



YOUR BEST DISINFECTION PLAYER

UV-TEAM is a versatile and effective addition to any transport and packaging lines including flow packs, thermoforming machines, sieves, cooling tunnels, automatic scales, and more.




- Improve product safety
- Extend shelf life
- Reduce the use of chemicals
- Meet disinfection standards
- Enhance product quality



UV-TEAM is widely used in food handling & processing, pharmaceutical R&D and production, and microbiological laboratories.

KEY PRODUCT FEATURES

- **Fits Any System**, a scalable form factor for providing any target level of disinfection.
- **Maximum Disinfection Performance**, with high-output UV-C lamps and mirror bright aluminum reflectors.
- **Built to Last**, made with robust AISI 304 stainless steel, carefully assembled and individually tested.
- **Thoughtfully Designed**, IP55 environmental protection. UVLON™ lamp protection available to protect broken glass and temperature fluctuations. **Cooling fan** to steady power output and extend ballast life.
- **Safety Automation**, shutter protection avoids exposure of personnel to the lamps and protects the device from maintenance and cleaning of production lines.
- **System Integration**, signals, alarms, and optional control board available to integrate with complex systems.



HEALTHCARE



HVAC



PROCESS
INDUSTRY



HOSPITALITY



SHARED
SPACES



PUBLIC
VENUS



WELLNESS
CENTERS



TRANSPORT

TECHNICAL TABLE	UV-TEAM-A-4P-3/65P	UV-TEAM-A-4P-3/172P
REPLACEMENT LAMP	N°3 GHA3-65W	N°3 GHA8-172W
POWER CONSUMPTION	220W	540W
DIMENSIONS (WxHxD)	mm 420 x 203 x 170 (in 16.53 x 7.99 x 6.69)	mm 906 x 203 x 170 (in 37.79 x 7.99 x 6.69)
WEIGHT	kg 4 lb 8.81	kg 8 lb 17.63
FOR ALL MODELS		
LAMP LIFE (hours)*	≤ 18.000	
PROTECTION RATING	IP55	
OP. TEMPERATURE**	min. -15°C ÷ max. +40°C (min. 5.0°F ÷ max. +104.0°F)	
OP. RELATIVE HUMIDITY**	From 20 to max. 90%	
V AC FREQUENCY	230V or 110-277V 50/60 Hz	
POWER SUPPLY	On-board power supply always included. Optional Control Board available.	
ELECTRICAL CONNECTION	Power supply cable, 3 m. lenght, with quick-connect panel socket/plug system (ILME) (IP67)	

* Continuous operation

** Outside of these ranges, performance may not be optimal

TROUBLE-FREE INTEGRATION AND INSTALLATION



- We provide the optimal point of integration for every product without requiring changes to your system.
- Mounting and powering the device can be done without complex requirements.
- Ongoing maintenance only takes a few minutes to replace lamps when necessary.

SOFTWARE ENGINEERED DISINFECTION

From our in-depth know-how on the subject and with our proprietary dosage calculation software we can simulate device performance and validate effectiveness in every application.

Calculation Software




TECHNICAL DRAWINGS

Every Light Progress Product is available in detailed DWG and STEP files for your design-in and specification clarity.

VIEW or DOWNLOAD now



MICROBIAL TESTS AND EFFICACY



Up-to log5 microbial load reduction, with a 5 seconds treatment at 10 cm from target Surface

Light Progress customers rely on our extensive history of third party testing and proven efficacy to meet any level of disinfection validated against literally any virus or microorganism.

We understand your need to meet Regulatory Requirements and Industrial Standards as we help you achieve microbial load reduction using our UV systems.

Light Progress Group SRL
Anghiari (AR)
ITALIA
P: (+39) 0575 749255
E: info@lightprogress.it
W: www.lightprogress.it

Light Progress GmbH
Aschaffenburg (BY)
DEUTSCHLAND
P: +49 176 761 42327
E: gmbh@lightprogress.it
W: www.lightprogress.de

Light Progress LLC
Dallas, (TX)
USA
P: (+1) 833-882-4255
E: americas@lightprogress.it
W: www.lightprogress.us

OFFICIALLY DISTRIBUTED BY: